PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 1 of 16 Print Date 06/10/2022

SAFETY DATA SHEET

PHANTOM GREY ACETAL UV

Section 1. Identification)n	
GHS product identifier	:	PHANTOM GREY ACETAL UV
Chemical name	:	Mixture
CAS number	:	Mixture
Other means of identification	:	CC10362164
Product type	:	solid
Relevant identified uses of the subs	tance	or mixture and uses advised against
Product use	:	Industrial applications. Plastics.
Supplier's details	:	AVIENT CORPORATION
		33587 Walker Road, Avon Lake, OH 44012
		1 (440) 930-1000 or 1 (844) 4AVIENT
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or
(with hours of operation)		accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	:	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

PHANTOM GREY ACETAL UV



Version Number 1.0 Revision Date 06/09/2022

Page 2 of 16 Print Date 06/10/2022

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	May cause damage to organs through prolonged or repeated exposure.
Precautionary statements Prevention	:	Not applicable. Do not breathe dust.
Response		Get medical advice or attention if you feel unwell.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.
		Not available.

Section 3. Composition/information on ingredients

:

:

:

Substance/mixture Chemical name Other means of identification Mixture Mixture CC10362164

CAS number/other identifiers

Ingredient name	%	CAS number
Phenol, 2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimethylpropyl)-	>= 3 - <= 5	25973-55-1
Carbon black	>= 0.3 - <= 1	1333-86-4
Titanium dioxide	>= 0.3 - <= 1	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022

ÀVIENT

Page 3 of 16 Print Date 06/10/2022

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects		
Eye contact Inhalation Skin contact Ingestion	:	No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards. No known significant effects or critical hazards.

Over-exposure signs/symptoms

ÀVIENT

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022 Page 4 of 16 Print Date 06/10/2022

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	In case of fire, use water spray (fog), foam, dry chemical or CO_2 . None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	If overheated or burnt, the polymer releases formaldehyde. Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



	Pa	ge	5	of	16
Print Da	te ()6/1	0/	20	22

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for contain	nment a	nd cleaning up
Small spill	:	Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures Advice on general occupational hygiene	:	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area,

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 6 of 16 Print Date 06/10/2022

away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Phenol, 2-(2H-benzotriazol-2-yl)-4,6- bis(1,1-dimethylpropyl)-	None.
Carbon black	OSHA PEL 1989 (1989-03-01) TWA 3.5 mg/m3 OSHA PEL (1993-06-30) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 3.5 mg/m3 NIOSH REL (1994-06-01) TWA 0.1 mgPAH/m ³ ACGIH TLV (2010-12-06) TWA 3 mg/m3 Form: Inhalable fraction
Titanium dioxide	OSHA PEL 1989 (1989-03-01) TWA 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) TWA 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TWA 10 mg/m3

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls :		Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
		6/16

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022

AVIENT

Page 7 of 16 Print Date 06/10/2022

Individual protection measures	
Hygiene measures Eye/face protection	 Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates this higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	 Based on the hazard and potential for exposure, select a respirator tha meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state Color	sol GR	id [Pellets.] EY
Odor Odor threshold		t available. t available.
Out in contra	• 10	t a vanaore.

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 8 of 16 Print Date 06/10/2022

рН	:	Not available.
Melting point	:	Not available.
Boiling point	:	Not available.
Flash point	:	Not available.
Burning time	:	Not available.
Burning rate	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive	:	Lower: Not available.
(flammable) limits		Upper: Not available.
Vapor pressure	:	Not available.
Vapor density	:	Not available.
Relative density	:	Not available.
Solubility	:	Not available.
Solubility in water	:	Not available.
Partition coefficient: n-	:	Not available.
octanol/water		
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
SADT	:	Not available.
Viscosity	:	Dynamic: Not available.
		Kinematic: Not available.
Aerosol product		
Heat of combustion	:	Not available.
Ignition distance	:	Not available.
Enclosed space ignition - Time	:	Not available.
equivalent		
Enclosed space ignition -	:	Not available.
Deflagration density		
Flame height	:	Not available.
Flame duration	:	Not available.

Section 10. Stability and reactivity

Reactivity	:	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Maintain polymer temperature below 230°C (446°F). Avoid prolonged exposure at or above recommended processing temperature.
Incompatible materials	:	Incompatible with strong oxidizers and with strong acids and bases

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 9 of 16 Print Date 06/10/2022

(decomposes to form formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin.

Hazardous decomposition products

. .

• • •

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

:

Product/ingredient name	Result	Species	Dose	Exposure	
Carbon black	·			•	
	LD50 Oral	Rat	15,400 mg/kg	-	
Titanium oxide (TiO2)	•			•	
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h	
	Dusts and mists				
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-	
Conclusion/Summary	: Mixture	e Not fully tested N	lo results available.		
Concrusion, Summary	· Wirktur	entor runy tested.	to results available.		
Irritation/Corrosion					
Conclusion/Summary					
Skin	: Mixture.Not fully tested.				
Eyes	: Mixture.Not fully tested.				
Respiratory	: Mixtur	·e.			
<u>Sensitization</u>					
Conclusion/Summary					
Skin	: Mixtur	e.Not fully tested.			
Respiratory		e.Not fully tested.			
N /					
<u>Mutagenicity</u>					
Conclusion/Summary	: Mixtur	e.Not fully tested.			

Information on toxicological effects

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022 Page 10 of 16 Print Date 06/10/2022

Carcinogenicity

Conclusion/Summary

Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Carbon black	-	2B	-
Titanium oxide (TiO2)	-	2B	-

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

:

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Phenol, 2-(2H-benzotriazol-2-yl)-	Category 2	oral	-
4,6-bis(1,1-dimethylpropyl)-			

Aspiration hazard

Not available.

Information on the likely routes of	:	Not available.
exposure		

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	No specific data.

ÀVIENT

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 11 of 16 Print Date 06/10/2022

Ingestion	:	No specific data.
Delayed and immediate effects and	also (chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Long term exposure		
Potential immediate effects Potential delayed effects	:	Not available. Not available.
Potential chronic health effects		
Conclusion/Summary	:	Mixture.Not fully tested.No results available.
General Carcinogenicity Mutagenicity Teratogenicity Developmental effects Fertility effects	::	May cause damage to organs through prolonged or repeated exposure. No known significant effects or critical hazards. No known significant effects or critical hazards.
Numerical measures of toxicity		
<u>Acute toxicity estimates</u> N/A		
Other information	:	This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Carbon black			
	Acute EC50 37.563 Mg/l Fresh	Daphnia - Daphnia magna	48 h
	water		
Titanium oxide (TiO2)			

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 12 of 16 Print Date 06/10/2022

	Acute LC50 > 1,000 Mg/l	Fish - Fundulus heteroclitus	96 h			
	Marine water					
	Acute LC50 3 Mg/l Fresh wa	ater Crustaceans - Ceriodaphnia dubia	48 h			
	Acute LC50 6.5 Mg/l Fresh water	Daphnia - Daphnia pulex	48 h			
PHANTOM GREY ACETAL U	JV					
Remarks - Acute - Aquatic invertebrates.:	Chemicals are not readily ava	Chemicals are not readily available as they are bound within the polymer matrix.				
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.					
Persistence and degradability						
Conclusion/Summary	: Chemicals are not readily available as they are bound within the polymer matrix.					
Conclusion/Summary	: Chemicals are no polymer matrix.	t readily available as they are bound v	within the			
Bioaccumulative potential Not available.						
Mobility in soil						
Soil/water partition coefficien (KOC)	at : Not available.					
Other adverse effects	: No known signifi	icant effects or critical hazards.				

Section 13. Disposal considerations

Disposal methods	:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be
------------------	---	---



PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022 Page 13 of 16 Print Date 06/10/2022

disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

U.S.DOT 49CFR Ground/Air/Water	:	Not regulated for transportation.
International Air ICAO/IATA	:	Consult mode specific transport rules
International Water IMO/IMDG	:	Consult mode specific transport rules

Section 15. Regulatory information

U.S. Federal regulations	 United States - TSCA 12(b) - Chemical export notification: None of the components are listed. United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(e) - Proposed significant new use rules: Not listed United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
	40/40

PHANTOM GREY ACETAL UV

Version Number 1.0 Revision Date 06/09/2022



Page 14 of 16 Print Date 06/10/2022

United States - TSCA 8(d) - Health and safety studies: Not listed
United States - EPA Clean water act (CWA) section 307 - Priority
pollutants: Not listed
United States - EPA Clean water act (CWA) section 311 Hazardous substances: Listed
United States - EPA Clean air act (CAA) section 112 - Accidental
release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental
release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental
release prevention - Toxic substances: Not listed
United States - Department of commerce - Precursor chemical:
Not listed

Clean Air Act Section 112(b)	:	Listed
Hazardous Air Pollutants (HAPs) Clean Air Act Section 602 Class I	:	Not listed
Substances		
Clean Air Act Section 602 Class II Substances	:	Not listed
DEA List I Chemicals (Precursor	:	Not listed
Chemicals) DEA List II Chemicals (Essential	:	Not listed
Chemicals)		

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

not applicable

SARA 311/312

Classification

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

Composition/information on ingredients

Name	%	Classification
Phenol, 2-(2H-benzotriazol-	>= 3 - <= 5	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
2-yl)-4,6-bis(1,1- dimethylpropyl)-		EXPOSURE) - oral - Category 2
Carbon black	>= 0.3 - <= 1	CARCINOGENICITY - Category 2
Titanium oxide (TiO2)	>= 0.3 - <= 1	CARCINOGENICITY - Category 2

Not applicable.

SAFETY DATA SHEET

PHANTOM GREY ACETAL UV



Version Number 1.0 Revision Date 06/09/2022

Page 15 of 16 Print Date 06/10/2022

State regulations		
Massachusetts	:	None of the components are listed.
New York	:	None of the components are listed.
New Jersey	:	The following components are listed: Carbon black Titanium dioxide
Pennsylvania	:	The following components are listed: Carbon black

Titanium dioxide

California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Carbon black	-	-
Titanium dioxide	-	-

United States inventory (TSCA 8b)	:	All components are active or exempted.
Canada inventory	:	All components are listed or exempted.
International regulations		
<u>Inventory list</u>		
Australia	:	All components are listed or exempted.
Canada	:	All components are listed or exempted.
China	:	All components are listed or exempted.
Europe inventory	:	All components are listed or exempted.
Japan	:	Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Turkey	:	Not determined.
United States	:	All components are active or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

PHANTOM GREY ACETAL UV



Version Number 1.0 Revision Date 06/09/2022 Page 16 of 16 Print Date 06/10/2022

Health	*	2
Flammability		0
Physical hazards		0
		ι

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual. History

<u>IIIStol y</u>		
Date of printing	:	06/10/2022
Date of issue/Date of revision	:	06/09/2022
Date of previous issue	:	00/00/0000
Version	:	1.0
Key to abbreviations	:	ATE = Acute Toxicity Estimate
•		BCF = Bioconcentration Factor
		GHS = Globally Harmonized System of Classification and Labelling of
		Chemicals
		IATA = International Air Transport Association
		IBC = Intermediate Bulk Container
		IMDG = International Maritime Dangerous Goods
		LogPow = logarithm of the octanol/water partition coefficient
		MARPOL = International Convention for the Prevention of Pollution From
		Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine
		pollution)
		UN = United Nations
References	:	Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.